(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 3 June 2004 (03.06.2004)

PCT

(10) International Publication Number WO 2004/047330 A1

(51) International Patent Classification7: H04L 25/08, H03K 5/1252

H04B 3/02,

(21) International Application Number:

PCT/IB2003/005164

(22) International Filing Date:

15 November 2003 (15.11.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/427,411 10/610,274

18 November 2002 (18.11.2002) US 30 June 2003 (30.06.2003) US

(71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): TOY, Edmond [US/US]; 1109 McKay Drive,, M/S-41SJ, San Jose, CA 95131 (US). DE LANGEN, Klaas-Jan [NL/US]; 1109 McKay Drive, M/S-41SJ, San Jose, CA 95131 (US).


- (74) Common Representative: KONINKLIJKE PHILIPS ELECTRONICS N.V.; c/o LESTER, Shannon, 1109 McKay Drive M/S-41SJ, San Jose, CA 95131 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE. AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH,

[Continued on next page]

(54) Title: DIGITAL FILTER CIRCUIT AND METHOD FOR BLOCKING A TRANSMISSION LINE REFLECTION SIGNAL



(57) Abstract: A digital blocking filter (120) and filtering method are provided for a device (100) receiving signals from a transmission line. The transmission line, which may comprise part of a complex bus system, is incompletely terminated, thereby resulting in a reflection signal within the line with transmission of a signal. The digital blocking filter (120) includes a pulse generator (140) for generating a masking pulse timed and of sufficient duration to substantially block at the device (100) the reflection signal, and logic (130) for combining the masking pulse and a received signal from the transmission line, thereby substantially blocking the reflection signal. Circuitry for handling reflection signals of various duration, as well as for substantially blocking a reflection signal on either a falling edge or a rising edge of a state change in the received signal are provided.